



कार्यालय, मुख्य निर्वाचन अधिकारी, दिल्ली
OFFICE OF THE CHIEF ELECTORAL OFFICER, DELHI

पुरानासेंटस्टीफनकॉलेजभवन,
कश्मीरीगेट, दिल्ली -110006,
फोननं.- 23946414
ईमेल- ceodelhi.hqr@gmail.com

Old St. Stephen's College Building,
Kashmere Gate, Delhi-10006.
Phone no- 23946414
Email: ceodelhi.hqr@gmail.com

No.25/ CEO/SVEEP/NIT/Bus Wrapping/2021

Dated:

C O R R I G E D U M

In partial modification of this office e-Tender, Tender ID No. 2021_CEO_208787_1 dated 24.9.2021, Notice for printing, Installation/Wrapping, maintenance and removal of Voter Awareness Materials/ Media Creative's on Buses/Cars etc. during various occasions such as Special Summary Revision, Lok Sabha/VidhanSabha Elections etc. floated on e-Tendering System of Govt. of NCT of Delhi on 24/9/2021; following corrections/amendments is being made:-

| Sl. No | Clause of Tender document | Content of tender document | Amended/updated content | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|--|--|--|-------------------------|--|-----------------|----------|------|-------|--------|-------|---------|-----------------|----------------------------|--------|-------------------------|--------|--------------------------|--------------------------------------|-------|---------------------------|----------------------------|--|-----------------|----------|-------------------------------------|--|
| 1 | 7(ii) | 3M Sheet-31J1220 with over-laminator Applicator will be used for wrapping of Buses/ Cars/Vans etc. | <p>The specification of material for wrapping of buses is as under:-</p> <p>Characteristics:</p> <table border="1"> <thead> <tr> <th colspan="2">(a) Physical Properties</th> </tr> <tr> <th>Characteristics</th> <th>Property</th> </tr> </thead> <tbody> <tr> <td>Film</td> <td>Vinyl</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>Surface</td> <td>Glossy or Matte</td> </tr> <tr> <td>Thickness without adhesive</td> <td>100 um</td> </tr> <tr> <td>Thickness with adhesive</td> <td>125 um</td> </tr> <tr> <td>Adhesive type and colour</td> <td>Acrylic Solvent-based, Clear or Grey</td> </tr> <tr> <td>Liner</td> <td>Polyethylene-coated paper</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">(b) Application Properties</th> </tr> <tr> <th>Characteristics</th> <th>Property</th> </tr> </thead> <tbody> <tr> <td>Graphic application recommendations</td> <td> Surface type: flat, simple, curves Substrate type: metal, paint, rigid, PVC Application Temperature: 40⁰ – 100⁰ F (4⁰- 38⁰ C) Air and substrate </td> </tr> </tbody> </table> | (a) Physical Properties | | Characteristics | Property | Film | Vinyl | Colour | White | Surface | Glossy or Matte | Thickness without adhesive | 100 um | Thickness with adhesive | 125 um | Adhesive type and colour | Acrylic Solvent-based, Clear or Grey | Liner | Polyethylene-coated paper | (b) Application Properties | | Characteristics | Property | Graphic application recommendations | Surface type: flat, simple, curves Substrate type: metal, paint, rigid, PVC Application Temperature: 40 ⁰ – 100 ⁰ F (4 ⁰ - 38 ⁰ C) Air and substrate |
| (a) Physical Properties | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics | Property | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Film | Vinyl | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Colour | White | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Surface | Glossy or Matte | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Thickness without adhesive | 100 um | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Thickness with adhesive | 125 um | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Adhesive type and colour | Acrylic Solvent-based, Clear or Grey | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Liner | Polyethylene-coated paper | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (b) Application Properties | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics | Property | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Graphic application recommendations | Surface type: flat, simple, curves Substrate type: metal, paint, rigid, PVC Application Temperature: 40 ⁰ – 100 ⁰ F (4 ⁰ - 38 ⁰ C) Air and substrate | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | |
|---|---|--|--|--|--|---|---|
| | | | <table border="1"> <tr> <td>Installed graphic exposure temperature</td> <td>-59⁰ - +192⁰ F (-50⁰ - +90⁰ C)</td> </tr> <tr> <td>Removability (apply on Alodine and heat age for 5 days at 66⁰ C</td> <td> Pull at 90⁰ : 30% Adhesive Residue Pull at 135⁰ : 0% Adhesive Residue Pull at 180⁰ : 40% Adhesive Residue </td> </tr> </table> | Installed graphic exposure temperature | -59 ⁰ - +192 ⁰ F (-50 ⁰ - +90 ⁰ C) | Removability (apply on Alodine and heat age for 5 days at 66 ⁰ C | Pull at 90⁰ : 30% Adhesive Residue Pull at 135⁰ : 0% Adhesive Residue Pull at 180⁰ : 40% Adhesive Residue |
| Installed graphic exposure temperature | -59 ⁰ - +192 ⁰ F (-50 ⁰ - +90 ⁰ C) | | | | | | |
| Removability (apply on Alodine and heat age for 5 days at 66 ⁰ C | Pull at 90⁰ : 30% Adhesive Residue Pull at 135⁰ : 0% Adhesive Residue Pull at 180⁰ : 40% Adhesive Residue | | | | | | |
| | | | Note: - Bidder should submit manufacturer certification with test report of material used. | | | | |
| 2 | Item No.2 of Financial Bid / (Annexure-VI) | Panel Clip rate per Sq. feet for printing, Installation, maintenance and removal of Voter Awareness Creative's/Media Creative's (advertisements via installation/wrapping of creative's /designs etc) on Buses/ Cars /Vans etc | Panel Clip rate per Sq. feet for printing, Installation, maintenance and removal of Voter Awareness Creative's/Media Creative's (advertisements via installation/wrapping of creative's /designs etc) on Buses/ Cars /Vans etc. The material Acrylic will be used for Panel clip. | | | | |
| 3 | Clause 7(iv),7(vi),7(x) and Item No.1 in Financial Bid (Annexure-VI) | "3M Sheet-31J1220 with over-laminator Applicator" | "vinyl sheet as specified in clause 7(ii) of tender document". | | | | |

(Lalit Mittal)
Election Officer (SVEEP)